

Versatile multimedia projector

The ViewSonic® PJ1158 delivers maximum impact for large-venue presentations. With 4000 LUMENS and 1000:1 contrast ratio (typ.), this PREMIUM PROJECTOR with optional lenses is ideally suited for conference rooms, lecture halls, religious institutions and boardrooms. The PJ1158 is fully-featured with a native XGA 1024 x 768 resolution, advanced image processing, manual lens shift, and horizontal and vertical (auto) keystone correction for perfect images. Network connectivity allows you to REMOTELY CONTROL AND MANAGE YOUR PRESENTATIONS and the 4 x 4-watt SRS® WOW STEREO SPEAKERS give your presentations powerful sound. The security bar and PIN lock guard against theft and unauthorised use. The PJ1158 is the fully-featured choice for dynamic presentations and smooth video entertainment in large venues.

PJ1158

**HIGH BRIGHTNESS
MULTIMEDIA PROJECTOR
WITH KEYSTONE CORRECTION**



SRS 
WOW

RAISING THE BAR ON YOUR PRESENTATIONS

> **Ultimate video source flexibility**

Connect two computers simultaneously or add a video source for dynamic meetings. Add another monitor output to view the same projected image on another display.

> **Network control through RJ-45**

Manage and monitor the projector remotely and receive e-mail alerts of projector and lamp status.

> **Enhanced security features**

PIN lock feature allows you to prevent unauthorised use. Kensington® security lock and a security bar allow you to secure the projector to deter theft.

> **The perfect image in any setting**

Digital horizontal and vertical (auto) keystone correction, manual lens shift, and optical zoom ensure the perfect image in any room.

> **Superior 16-watt stereo sound**

Four 4-watt speakers with SRS® WOW technology for panoramic 3D sound.

> **Easy maintenance**

Easy access to the lamp and filter covers even when the projector is mounted.

> **Optional lenses make installation flexible**

Easy-to-install bayonet lens options allow you to project in rooms of virtually any size.



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic 
the choice of professionals

PJ1158

HIGH BRIGHTNESS MULTIMEDIA PROJECTOR WITH KEYSTONE CORRECTION

ViewSonic 

the choice of professionals



PROJECTOR	Type	3 x 0.8" P-Si TFT active matrix with MLA
	Resolution	1024 x 768 XGA native, (max. 1600 x 1200 UXGA compressed)
	Lens	Manual zoom, manual focus, manual lens shift (TBA)
	Zoom Factor	1.2 (F = 1.7–2.1/f = 24.3mm–29.2mm)
	Digital Keystone	Vertical ± 40°, horizontal ± 20°
DISPLAY	Size	30"–300" (0.76m–7.62m) (Diagonal)
	Throw Distance	0.9m–13m
	Throw Ratio	1.5~1.8:1
	Lamp	285W UHB, 2000 hours ¹
	Brightness	4000 ANSI lumens (typ.)
	Contrast Ratio	1000:1
	Aspect Ratio	4:3 (native), 16:9
AUDIO	Speaker	4 x 4-watt with SRS [®] WOW technology (virtual surround-sound)
INPUT SIGNAL	Video	RGB analogue, NTSC M, NTSC 4.43, PAL, SECAM, SDTV/EDTV (480i/p, 576i/p), HDTV (720p, 1080i)
	Frequency	Fh: 31–92kHz; Fv: 56–120Hz
COMPATIBILITY	PC	Analogue: VGA up to UXGA (compressed), 1024 x 768 @ 60Hz preferred
	Mac ^{®2}	Analogue: up to SXGA (scaled), 1024 x 768 @ 60Hz preferred
CONNECTOR	PC-RGB (in)	2 x 15-pin mini D-sub
	PC-RGB (out)	1 x 15-pin mini D-sub
	Digital	1 x M1-D (DVI plus USB support)
	Composite Video	1 x RCA jack
	S-Video	1 x 4-pin mini-DIN
	Component Video	1 x RCA set (YPbPr)
	Audio (in)	2 x 3.5mm stereo mini jack (for PC), 2 x RCA set L/R jack (for video)
	Audio (out)	1 x 3.5mm stereo mini jack
	USB	Integrated into universal digital M1-D connector (for mouse control)
	Control	1 x 9-pin D-sub RS-232
	Network	1 x RJ-45
POWER	Voltage	AC 100-264V, 50/60Hz (auto switch)
	Consumption	460W (typ.)
CONTROLS	Basic	Stand-by, menu, input, reset, H/V keystone correction, search, focus, zoom, volume
	OSD	Language, colour balance (R, G, B), sharpness, colour, tint, H/V position, H phase, H size, overscan, colour space, component 3-D-YCS, video NR, PinP input, PinP position, power up input, information, S2-aspect, adjust, power off, power on, search, blank, start up, My screen, My screen size, My screen lock, auto off, audio (volume, speaker, mute), menu position, message
OPERATING CONDITIONS	Temperature	5°C–35°C
	Humidity	10%–85% (non condensation)
NOISE LEVEL	Normal	36dB (typ.)
	Eco mode	30dB (typ.)
DIMENSIONS	(W x H x D mm)	418 x 140 x 320 (physical) 555 x 244 x 478 (packaging)
WEIGHT	Net	7.1kg
	Gross	11.6kg
REGULATIONS		CE, CB, TÜV/GS, GHOST, UL60950, C-UL, FCC B, C-Tick, NOM, CCC, PSB, WEEE, RoHS
PACKAGE CONTENTS		Projector, power cables, VGA cable, AV cable, remote control, batteries, lens cap, Quick Start Guide (multi-language), ViewSonic Wizard CD (User guide) (multi-language)
OTHER		Lens shift, progressive scan, PIN lock, network control, anti-theft security bar, daylight mode, 16-watt speakers, optional lenses
WARRANTY		Please see: www.viewsoniceurope.com/UK/Support/warranty.htm

OPTIONAL ACCESSORIES

- > Replacement lamp RLC-021
- > Universal ceiling mount kit WMK-005
- > Stackable ATA hard shipping case CASE-003
- > Short throw zoom lens TBD
- > Long throw zoom lens TBD

ISO 9001



ISO 14001



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Europe Limited/UK

ViewSonic House
Fleming Way, Crawley
West Sussex, RH10 9GA
United Kingdom

Tel: +44 (0) 12 93 64 39 00
Fax: +44 (0) 12 93 64 39 10

ViewSonic Germany

Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany

Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France

Parc des Barbanniers
1 allée des Bas Tilliers
92230 Gennevilliers
France

Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation

381 Brea Canyon Road
Walnut
California 91789-0708
USA

Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Belux

ViewSonic Denmark

ViewSonic Finland

ViewSonic Italy

ViewSonic MEA

ViewSonic Netherlands

ViewSonic Norway

ViewSonic Spain

ViewSonic Sweden

Tel: +32 (0)56 85 26 27
Tel: +45 70 22 11 71
Tel: +358 (0)9 5406 4070
Tel: +39 02 73 95 50 22
Tel: +971 (0) 4 88 11 871
Tel: +31 (0)20 491 9254
Tel: +47 (0) 22 88 17 60
Tel: +34 (0) 91 63 05 339
Tel: +46 (0) 8 50 71 30 00

¹ Running Eco mode exclusively can extend lamp life. ² May require optional Mac adapter.

Copyright © 2006 ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. VS PJ1158-1 09/06-UK

For more product information, visit us on the web at www.ViewSonicEurope.com