VA703b

17" VALUE SERIES LCD MONITOR WITH 8MS VIDEO RESPONSE

Reliable performance in a stylish design

No matter if you use it for entertainment in the home or for intensive graphics tasks, ViewSonic's 17" VA703b fits the bill perfectly. Thanks to an 8ms video response time, depictions of movies, games or scrolling text will impress with their smooth, full-motion. A 600:1 contrast ratio (typ.) and 280cd/m² of brightness (typ.) lends this elegantly-designed model great display quality in vivid, true-to-life colour. Screen adjustments are child's play via the OSD and can be safely locked in. This slim bezel LCD is VESA® compliant – it will also look great mounted on your wall. In addition, Kensington® security port theft deterrence will ensure your investment is effectively protected. The VA703b LCD display provides outstanding performance for any application.

It's not just a great value LCD. It's a ViewSonic.



IMPRESSIVE PERFORMANCE WITHOUT THE HIGH PRICE TAG

- > ClearMotiv[™] 8ms video response time Ultra-fast 8ms video response delivers broadcast-quality full motion video.
- > Dynamic Structure™ technology Innovative liquid crystal composition and pixel matrix accelerate video response for seamless video and intense graphics.
- > Very-high brightness and contrast 280cd/m² brightness (typ.) and 600:1 contrast ratio (typ.) for rich, detailed images.
- Full 17" Viewable screen with 1280 x 1024 resolution Displays a full, flat 17" viewable area with crisp details and fully saturated colours.
- Stylish slim-bezel design
 An ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > OnView[®] controls for superior screen adjustability Screen adjustments are precisely made via an easy-to-use on-screen menu.
- OSD/Power lock secures your settings
 Prevents changes to monitor settings and maintains an optimised image.
- > Integrated power supply
- > VESA® 100mm wall mount interface and Kensington® security port
- > PC and Mac° compatible
- > TCO'03 and EnergyStar™ qualified



VIEWSONIC PRODUCTS, PROGRAMS, AND SERVICES





VA703b

17" VALUE SERIES LCD MONITOR WITH 8MS VIDEO RESPONSE





DISPLAYS		
	ISO 14001	

Tto isoment

FM 40187 EMS 4096 I Sistemi di Gestione Qualità e Gr di ViewSonic Corporation sono ISO 9001 e ISO 14001 dalla British

LCD	Type Display Area Pixel Pitch Optimum Resolution Pixel Clock Contrast Ratio Viewing Angle Response Time Colour Support Light Source Brightness Panel Surface	 17" TN colour TFT active matrix XGA LCD 33.8cm horizontal x 27.0cm vertical; 43.2cm diagonal 0.264mm 1280 x 1024@60Hz 135MHz 600:1 (typ.) 150° horizontal, 135° vertical (at 10:1) 170° horizontal, 155° vertical (at 5:1) 8ms (off-on-off) (typ.) 16.2M colours (6-bit + 2-bit FRC) Long life, 50000 hrs. (min.) 280cd/m² (typ.) Anti-glare (3H)
VIDEO INPUT	Analogue Frequency Synchronisation	RGB analogue (0.7 Vp-p, 75 ohm) $F_h: 30 - 82kHz, F_v: 50 - 85Hz$ H/V separate (TTL)
COMPATIBILITY	PC Mac ^{®1}	VGA up to 1280 x 1024 non-interlaced (@60Hz preferred) Power Mac™ up to 1280 x 1024 non-interlaced (@60Hz preferred)
CONNECTOR	Analogue Power	15-pin mini D-Sub (attached cable) 3-pin AC plug (CEE22)
POWER	Voltage Consumption	AC 100 – 240V, 50/60Hz (auto switch), internal power supply <36 watt (max.), <1 watt in power save mode
ERGONOMICS	Tilt	Down 5°, Up 20°
CONTROLS	Basic OSD	Power, menu [1], up, down, select [2] Auto image adjust, contrast, brightness, ViewMatch® colour adjust (sRGB, 9300K, 6500K, 5400K, user RGB), information (resolution, H/V frequency, pixel clock, model number, serial number, website), manual image adjust (H/V position, H size, fine tune, sharpness), setup menu (language [English, Finnish, French, German, Italian, Japanese, Spanish, Simplified Chinese, Traditional Chinese], resolution notice, OSD position, OSD timeout, OSD background), OSD/power lock, memory recall
OPERATING CONDITONS	Temperature Humidity	0°C – 40°C 10% – 90% (non-condensation)
DIMENSIONS	(W x H x D mm)	379 x 400 x 210 (with stand)
WEIGHT	Net Gross	3.6kg (with stand) 4.8kg
REGULATIONS		TCO'03, CE, CB, TÜV/GS, TÜV/Ergo, ISO13406-2 (pixel failure class II), UL/cUL, FCC-B, NOM, GOST-R, ENERGY, BSMI, CCC, (PSB), (C-TICK), Green Mark, WEEE, RoHS
POWER MANAGEMENT		Meets TCO'03 and ENERGY standards
SECURITY		Kensington® security port
WALL MOUNT		VESA FDMI 100mm x 100mm
PACKAGE		LCD Monitor, power cable, 15-pin VGA video cable, Quick Start Guide, ViewSonic Wizard CD-ROM (User Guide/drivers)
WARRANTY		Please see: www.viewsoniceurope.com/UK/Support/warranty.htm

ViewSonic Europe Limited/UK

ViewSonic House Fleming Way, Crawley West Sussex, RH10 9GA United Kingdom

Tel: +44 (0) 12 93 64 39 00 Fax: +44 (0) 12 93 64 39 10

Hanns-Martin-Schleyer-Straße 18A 47877 Willich Germany

ViewSonic Germany

Tel: +49 (0) 21 54 91 88 0 Fax: +49 (0) 21 54 91 88 10

ViewSonic France Parc des Barbanniers allée des Bas Tilliers 92230 Gennevilliers Tel: +33 (0) 1 41 47 49 00 Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation 381 Brea Canyon Road Walnut California 91789-0708 USA Tel: +1 909 869 7976 Fax: +1 909 869 7958

Tel: +32 (0)56 85 26 27 Tel: +45 70 22 11 71 ViewSonic Belux ViewSonic Denmark ViewSonic Finland Tel: +358 (0)9 5406 4070 ViewSonic Italy ViewSonic MEA Tel: +39 02 73 95 50 22 Tel: +971 (0) 4 88 11 871 ViewSonic Netherlands Tel: +31 (0)20 491 9254 ViewSonic Norway Tel: +47 (0) 22 88 17 60 Tel: +34 (0) 91 63 05 339 ViewSonic Spain ViewSonic Sweden Tel: +46 (0) 8 50 71 30 00

¹May require optional Mac adapter.

Copyright © 2006, ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. VS VA703b-07/06-UK

France