

# VA2012w-2

**20" WIDE-SCREEN LCD**

**WITH 8MS CLEARMOTIV™**

## Tantalising visual experience

The ViewSonic VA2012w-2 20.1" LCD is packed with an IMPRESSIVE ARRAY OF FEATURES TO ENHANCE YOUR WORK AND PLAY – and the budget-friendly price makes it an even more tantalising package. The 16:10 wide-screen aspect ratio provides more productive space for multiple windows, HD-format video and immersive gaming action. This feature-rich display includes ViewSonic's innovative Dynamic Structure™ technology and ClearMotiv™ 8ms video response for SMOOTH VIDEO AND INTENSE GRAPHICS. The 300cd/m<sup>2</sup> of brightness, 600:1 contrast ratio as well as 1680 x 1050 optimum resolution ensure crystal-clear images and crisp text. It's a stylish wide-screen LCD that upgrades your workspace while staying within your budget.

**It's not just another wide-screen LCD. It's a ViewSonic.**



### ELEGANTLY DESIGNED, AFFORDABLY PRICED

> **Wide-screen Performance for Business**

Wide-screen format is ideally suited for document handling, displaying multiple pages, greater workability with spreadsheets and more. Improve your business productivity and save time with the VA2012w-2.

> **Wide-screen Experience for Entertainment**

Immerse yourself with full wide-screen views for intense gaming action.

> **Wide-screen Experience for Movies**

Experience movies in wide-screen format – the 16:10 aspect ratio delivers the ultimate in video performance.

> **Award Winning Performance**

See the difference with ViewSonic's award winning screen performance. 300cd/m<sup>2</sup> brightness levels and 600:1 contrast ratios deliver rich, crisp, detailed images. 8ms response time provides fluid, high-quality video performance.

> **Multimedia Versatility**

For games, movies and even office applications, the built in stereo speakers deliver high quality audio.



**VIEWSONIC**  
PRODUCTS, PROGRAMS,  
AND SERVICES

# VA2012w-2

## 20" WIDE-SCREEN LCD WITH 8MS CLEARMOTIV™



<b>LCD</b>	Type	20.1" TN colour TFT active matrix WSXGA+ LCD
	Display Area	43.3cm horizontal x 27.1cm vertical; 51.1cm diagonal
	Pixel Pitch	0.258mm
	Bandwidth	205MHz analogue
	Optimum Resolution	1680 x 1050
	Contrast Ratio	600:1 (typ.)
	Viewing Angles	140° horizontal, 125° vertical (at 10:1) 160° horizontal, 145° vertical (at 5:1)
	Response Time	8ms (off-on-off) (typ.)
	Colour Support	16.7M colours (8-bit)
	Light Source	Long life, 40000 hrs. (min. typ.)
	Brightness	300 cd/m <sup>2</sup> (typ.)
	Aspect Ratio	16:10
	Panel Surface	Anti-glare (3H)
<b>VIDEO INPUT</b>	Analogue	RGB analogue (0.7/1.0 Vp-p, 75 ohms)
	Frequency	Fh: 30 - 94kHz, Fv: 50 - 75Hz
	Synchronisation	H/V separated (TTL)
<b>COMPATIBILITY</b>	PC	VGA up to 1680 x 1050 non-interlaced (max. 60Hz)
	Mac <sup>®1</sup>	Power Mac™ up to 1680 x 1050 (max. 60Hz)
<b>CONNECTOR</b>	Analogue	15-pin mini D-sub (detachable cable)
	Audio	3.5mm stereo audio line-in
	Power	3-pin AC plug (CEE22)
<b>AUDIO</b>	Speakers	Integrated stereo speakers
<b>POWER</b>	Voltage	AC 100 – 240V, 50/60Hz (auto switch), internal power supply
	Consumption	47 watt (typ.), <2 watt in power save mode
<b>ERGONOMICS</b>	Tilt	Down 5°, up 20°
<b>CONTROLS</b>	Basic	Power, menu [1], down, up, select [2], mute, volume up/down, main power
	OSD	Auto image adjust, contrast, brightness, ViewMatch® colour adjust (sRGB, 9300K, 6500K, 5400K, user RGB), information (resolution, H/V frequency, pixel clock, model number, serial number, website), manual image adjust (H. size, H/V position, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), OSD/power lock, memory recall
<b>OPERATING CONDITIONS</b>	Temperature	0°C – 40°C
	Humidity	10% – 90% (non-condensing)
<b>DIMENSIONS</b>	(W x H x D mm)	479 x 423 x 216 (w/ stand) 479 x 351 x 63 (w/o stand)
<b>WEIGHT</b>	Net	5.5kg (w/ stand); 4.9kg (w/o stand)
<b>REGULATIONS</b>		TCO'99, TÜV/GS, TÜV/Ergo, ISO 13406-2 (pixel failure class II), TÜV-S, UL, cUL, FCC-B, CB, CE, NOM, GOST-R (Hygienic), SASO, PCBC, BSMI, CCC, Green Mark, Energy Star®, (PSB), (C-TICK), MIC
<b>POWER MANAGEMENT</b>		Meets TCO'99 and Energy Star® standards
<b>PACKAGE CONTENTS</b>		LCD display, power cable, 15-pin VGA cable, audio cable, Quick Start Guide, ViewSonic Wizard CD (User Guide/drivers)
<b>WARRANTY</b>		Please see: <a href="http://www.viewsoniceurope.com/UK/Support/warranty.htm">www.viewsoniceurope.com/UK/Support/warranty.htm</a>



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

**ViewSonic Europe Limited/UK**  
ViewSonic House  
Fleming Way, Crawley  
West Sussex, RH10 9GA  
United Kingdom

Tel: +44 (0) 12 93 64 39 00  
Fax: +44 (0) 12 93 64 39 10

**ViewSonic Germany**  
Hanns-Martin-Schleyer-Straße 18A  
47877 Willich  
Germany

Tel: +49 (0) 21 54 91 88 0  
Fax: +49 (0) 21 54 91 88 10

**ViewSonic France**  
Parc des Barbanniers  
1 allée des Bas Tilliers  
92230 Gennevilliers  
France

Tel: +33 (0) 1 41 47 49 00  
Fax: +33 (0) 1 41 47 49 10

**ViewSonic Corporation**  
381 Brea Canyon Road  
Walnut  
California 91789-0708  
USA

Tel: +1 909 869 7976  
Fax: +1 909 869 7958

**ViewSonic Benelux**  
**ViewSonic Denmark**  
**ViewSonic Finland**  
**ViewSonic Italy**  
**ViewSonic MEA**  
**ViewSonic Norway**  
**ViewSonic Spain**  
**ViewSonic Sweden**

Tel: +32 056/85 26 27  
Tel: +45 70 22 11 71  
Tel: +358 (0)9 5406 4070  
Tel: +34 (0) 91 63 05 339  
Tel: +971 (0) 4 88 11 871  
Tel: +47 (0) 22 88 17 60  
Tel: +34 (0) 91 63 05 339  
Tel: +46 (0) 8 50 71 30 00

<sup>1</sup> May require optional Mac adapter.