

## Elegantly-styled wide-screen LCD monitor

ViewSonic's 19" VG1921wm LCD monitor combines wide-screen performance and elegant two-tone style. Improve productivity and save time with wide-screen versatility. Display multiple pages, larger spreadsheets and more on a single screen without the need to swap. Enjoy high brightness and contrast levels for rich, precise, detailed images and razor sharp text. Built-in stereo speakers deliver high quality sound performance. VESA wall-mount compliance and integrated Kensington security port offer flexibility and safety for your investment. The elegantly designed VG1921wm wide-screen monitor is the ideal business LCD monitor.

**It's not just a wide-screen LCD monitor. It's a ViewSonic**

# VG1921wm

**19" WIDE-SCREEN LCD**

WITH CLEARMOTIV™ 5MS BROADCAST  
QUALITY VIDEO



### STYLE AND PERFORMANCE FOR DEMANDING PROFESSIONALS

- > **Wide-screen performance for business**  
Improve productivity and performance with wide-screen format. Display multiple pages, larger spreadsheets and more on a single screen without the need to swap.
- > **Award-winning performance**  
See the Difference with ViewSonic's award-winning screen performance. 700:1 contrast levels and 300cd/m<sup>2</sup> deliver rich, crisp, detailed images.
- > **Stylish slim-bezel design**  
Ultra-modern thin bezel design lets you see more without taking up valuable desktop real estate.
- > **ClearMotiv™ 5ms video response time**  
Super fast 5ms video response time delivers fluid flowing images.
- > **Multimedia enhanced**  
Built-in stereo speakers deliver high-quality audio performance.
- > **Full 19" wide-screen display with 1440 x 900 resolution**
- > **Kensington® security port**  
Provides theft deterrence and the OSD and power lock prevent unauthorised screen changes.
- > **PC and Mac® compatible**



# VG1921wm

## 19" WIDE-SCREEN LCD MONITOR WITH 5MS CLEARMOTIV™ BROADCAST QUALITY



<b>LCD</b>	Type	19" Wide TN colour TFT active matrix WXGA+ LCD
	Display Area	41.0cm horizontal x 25.6cm vertical; 48.3cm diagonal
	Pixel Pitch	0.285mm
	Optimum Resolution	1440 x 900@60Hz
	Pixel Clock	140MHz
	Contrast Ratio	700:1 (typ.)
	Viewing Angle	160° horizontal, 140° vertical (at 10:1) 160° horizontal, 160° vertical (at 5:1)
	Response Time	5ms (off-on-off) (typ.)
	Colour Support	16.2M colours (6-bit+2-bit FRC)
	Light Source	Long life, 40000 hrs. (min.)
	Brightness	300cd/m <sup>2</sup>
	Aspect Ratio	16:10
	Panel Surface	Anti-glare (3H)
<b>VIDEO INPUT</b>	Analogue	RGB analogue (0.7/1.0 Vp-p, 75 ohm)
	Frequency	Fh: 30–82kHz, Fv: 56–75Hz
	Synchronisation	H/V separate (TTL)
<b>COMPATIBILITY</b>	PC	VGA up to 1440 x 900 non-interlaced
	Mac <sup>®1</sup>	Power Mac™ up to 1440 x 900 non-interlaced
<b>CONNECTOR</b>	Analogue	15-pin mini D-Sub (detachable cable)
	Audio	3.5mm stereo audio line-in
	Power	3-pin AC plug (CEE22)
<b>AUDIO</b>	Speakers	2 x 1.5 watt integrated stereo speakers
<b>POWER</b>	Voltage	AC 100–240V, 50/60Hz (auto switch), internal power supply
	Consumption	35 watt (typ.), <1 watt in power save mode
<b>ERGONOMICS</b>	Tilt	Down 5°, Up 20°
<b>CONTROLS</b>	Basic	Power, menu [1], up, down, select [2], mute
	OSD	Auto image adjust, contrast, brightness, audio (volume, mute), ViewMatch <sup>®</sup> colour adjust (sRGB, 9300K, 6500K, 5400K, user RGB), information (resolution, H/V frequency, pixel clock, model number, serial number), manual image adjust (H/V position, H size, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), OSD/power lock, memory recall
<b>OPERATING CONDITIONS</b>	Temperature	5°C–35°C
	Humidity	20%–80% (non-condensation)
<b>DIMENSIONS</b>	(W x H x D mm)	460 x 416 x 206 (with stand) 460 x 352 x 62 (without stand) 534 x 509 x 150 (packaging)
<b>WEIGHT</b>	Net	5.0kg (with stand)
	Gross	6.5kg
<b>REGULATIONS</b>		TCO'03, TÜV/GS, TÜV/Ergo, ISO13406-2 (pixel failure class II), CE, CB, GOST-R, PSB, Energy Star, YCO03, UL/cUL, FCC-B, ICES 003, NOM, Argentina-TÜV/S, SASO, BSMI, C-Tick, MIC, CCC, WEEE, RoHS
<b>POWER MANAGEMENT</b>		Meets TCO'03 and Energy Star <sup>®</sup> standards
<b>SECURITY</b>		Kensington <sup>®</sup> security port
<b>WALL MOUNT</b>		VESA FDMI 75mm x 75mm
<b>PACKAGE CONTENT</b>		LCD Monitor, power cable, D-sub video cable, audio cable, Quick Start Guide, ViewSonic Wizard CD-ROM (User Guide/drivers) (multi-language)
<b>WARRANTY</b>		Please see: <a href="http://www.viewsoniceurope.com/UK/Support/warranty.htm">www.viewsoniceurope.com/UK/Support/warranty.htm</a>



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

### ViewSonic Europe Limited/UK

ViewSonic House  
Fleming Way, Crawley  
West Sussex, RH10 9GA  
United Kingdom

Tel: +44 (0) 12 93 64 39 00  
Fax: +44 (0) 12 93 64 39 10

### ViewSonic Germany

Hanns-Martin-Schleyer-Straße 18A  
47877 Willich  
Germany

Tel: +49 (0) 21 54 91 88 0  
Fax: +49 (0) 21 54 91 88 10

### ViewSonic France

Parc des Barbannières  
1 allée des Bas Tilliers  
92230 Gennevilliers  
France

Tel: +33 (0) 1 41 47 49 00  
Fax: +33 (0) 1 41 47 49 10

### ViewSonic Corporation

381 Brea Canyon Road  
Walnut  
California 91789-0708  
USA

Tel: +1 909 869 7976  
Fax: +1 909 869 7958

### ViewSonic Belux

ViewSonic Denmark

ViewSonic Finland

ViewSonic Italy

ViewSonic MEA

ViewSonic Netherlands

ViewSonic Norway

ViewSonic Spain

ViewSonic Sweden

Tel: +32 (0)56 85 26 27  
Tel: +45 70 22 11 71  
Tel: +358 (0)9 5406 4070  
Tel: +39 02 73 95 50 22  
Tel: +971 (0) 4 88 11 871  
Tel: +31 (0)20 491 9254  
Tel: +47 (0) 22 88 17 60  
Tel: +34 (0) 91 63 05 339  
Tel: +46 (0) 8 50 71 30 00

<sup>1</sup> May require optional Mac adapter.

Copyright © 2006, ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. VS VG1921wm-2 08/06-UK