VG1930wm 19" WIDESCREEN GRAPHICS SERIES LCD

WITH SWIVEL AND HEIGHT ADJUST

Elegantly styled digital business widescreen

ViewSonic's 19" VG1930wm combines WIDESCREEN and multimedia performance with ergonomic flexibility. Improve productivity and save time with widescreen versatility. Display multiple pages, larger spreadsheets and more on a single screen without the need to swap. HEIGHT ADJUSTMENT, tilt and 360° swivel features allow the user to set the ergonomic position of the monitor to generate the best possible viewing position. Enjoy high brightness and contrast levels for rich, precise, detailed images and razor sharp text, whilst DIGITAL AND ANALOGUE inputs ensure maximum connectivity options. Built-in stereo-speakers deliver high quality audio performance. The elegantly designed VG1930wm widescreen monitor is the ideal business LCD.

It's not just a digital widescreen LCD monitor. It's a ViewSonic.



FAST, WIDESCREEN DISPLAY

> Stylish slim-bezel design

The full 19" viewable widescreen in an ultra-thin bezel lets you see more without taking up valuable desktop real estate.

> Ergonomic base adds ease and comfort

Ultimate ergonomic flexibility comes built-in with the convenient 80mm height adjustment and 360° swivel base.

- > High 300cd/m² brightness (typ.) and 700:1 contrast ratio (typ.)
- > ClearMotiv™ 5ms video response time
- Fast 5ms video response delivers broadcast-quality video.
- > Dynamic Structure™ technology
 Innovative liquid crystal composition and pixel matrix accelerate video response for seamless video and intense graphics.
- > OptiSync® digital/analogue inputs expand your connectivity Multi-mode input technology supports both digital (DVI) and analogue (VGA) signals for ultimate compatibility and configuration flexibility.
- > Multimedia enhanced
 - Save workspace and enjoy rich stereo sound with two built-in stereo speakers.
- > VESA 75mm wall mount interface and Kensington® security port
- > TCO'03 and ENERGY STAR® qualified
- > PC and Mac® compatible





VG1930wm

19" WIDESCREEN GRAPHICS SERIES LCD WITH SWIVEL AND HEIGHT ADJUST















LCD	Type Display Area Pixel Pitch Optimum Resolution Pixel Clock Contrast Ratio Viewing Angles Response Time Light Source Brightness	19" Wide TN colour TFT active matrix WXGA+ LCD 41.0cm horizontal x 25.6cm vertical, 48.3cm diagonal 0.285mm 1440 x 900@60Hz 135MHz 700:1 (typ.) 160° horizontal, 160° vertical (at 10:1) 170° horizontal, 170° vertical (at 5:1) 5ms (off-on-off) (typ.) Long life, 40000 hrs. (typ.) 300cd/m² (typ.)	
	Panel Surface	Anti-glare	
VIDEO INPUT	Analogue Digital Frequency Synchronisation	RGB analogue (0.7 Vp-p, 75 ohm) DVI-D (TMDS, 100 ohm) Fh: 24~82kHz, Fv: 50~75Hz H/V separated (TTL) (screen-on-screen)	
COMPATIBILITY	PC Mac ^{®1}	VGA up to 1440 x 900 non-interlaced Power Mac™ G3/G4/G5 up to 1440 x 900	
CONNECTOR	Analogue Digital Audio Power	15-pin mini D-Sub (detachable cable) 24-pin DVI-D (detachable cable) 3.5mm stereo audio line-in 3-pin AC plug (CEE22)	
AUDIO	Speakers Amplifier	2 x 1.5-watt integrated speakers 1.5-watt @ THD < 8%	
POWER	Voltage Consumption	AC 100–240V, 50/60Hz (auto switch), internal power supply 35 watt (typ.), <1 watt in power save mode	
ERGONOMICS	Tilt Swivel Height Adjustment	Down 5°, Up 20° 360° swivel base 0~80mm	
CONTROLS	Basic OSD ²	Power, menu [1], up, down, select [2], mute, volume up/down Auto image adjust, contrast, brightness, input select (D-sub, DVI-D), View Match® colour adjust (sRGB, 9300K, 7500K, 6500K, 5400K), information (resolution, H/V frequency, pixel clock, model number, serial number), manual image adjust (H/V position, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall	
OPERATING CONDITIONS	Temperature Humidity	0°C-40°C 10%-90% (non-condensing)	
DIMENSIONS	W x H x D mm	460 x 434–514 x 230 (with stand) 460 x 352 x 61 (without stand) 560 x 525 x 282 (packaging)	
WEIGHT	Net Gross	5.4kg (with stand) 6.9kg	
REGULATIONS		TCO'03, TÜV/GS, TÜV/ERGO, ISO 13406-2 (pixel failure class II), CB, CE, GOST-R, UL, cUL, FCC-B, ICES-003, SASO, ENERGY STAR®, C-Tick, BSMI PSB, Argentina TÜV-S, MPR II, VCCI, CCC, WEEE, RoHS	
SECURITY		Kensington® security port	
WALL MOUNT		VESA FDMI 75mm x 75mm	
POWER MANAGEMENT		Meets TCO'03 and ENERGY STAR® standards	
PACKAGE CONTENTS		LCD display, VGA cable, power cable, audio cable, Quick Start Guide, ViewSonic Wizard CD-ROM (User Guide/drivers) (multi-language)	
WARRANTY		Please see: www.viewsoniceurope.com/UK/Support/warranty.htm	

viewsonic Europe Emitted/OK	viewsonic derinary	viewsonic i rance
ViewSonic House	Hanns-Martin-Schleyer-Straße 18A	Parc des Barbanniers

Fleming Way, Crawley West Sussex, RH10 9GA United Kingdom 47877 Willich Germany

Tel: +44 (0) 12 93 64 39 00 Fax: +44 (0) 12 93 64 39 10 Tel: +49 (0) 21 54 91 88 0 Fax: +49 (0) 21 54 91 88 10

ViewSonic Corporation 381 Brea Canyon Road Walnut allée des Bas Tilliers 92230 Gennevilliers USA France Tel: +33 (0) 1 41 47 49 00 Fax: +33 (0) 1 41 47 49 10

California 91789-0708 Tel: +1 909 869 7976 Fax: +1 909 869 7958

ViewSonic Belux ViewSonic Denmark ViewSonic Finland ViewSonic Italy ViewSonic MEA ViewSonic Netherlands ViewSonic Norway ViewSonic Spain ViewSonic Sweden

Tel: +32 (0)56 85 26 27 Tel: +45 70 22 11 71 Tel: +358 (0)9 5406 4070 Tel: +39 02 73 95 50 22 Tel: +971 (0) 4 88 11 871 Tel: +31 (0)20 491 9254 Tel: +47 (0) 22 88 17 60 Tel: +34 (0) 91 63 05 339 Tel: +46 (0) 8 50 71 30 00

Copyright © 2006, ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. VS VG1930wm 10/06-UK

¹May require optional Mac adapter. ² Some features may not available on all inputs.