

Speed, simplicity and sound

Treat yourself to a master stroke of aesthetic design. The 19" ViewSonic VX912 impresses with its pure lines elegant simplicity – without sacrificing performance: HIGH BRIGHTNESS AND CONTRAST values deliver EXCELLENT IMAGE QUALITY and a response time of just 5ms lends films, games and DVDs excellent fluid motion. A set of stereo speakers are cleverly hidden within the casing and this model is additionally equipped with both an analogue and digital input. This high-tech monitor is just the shot for demanding home or business users.

VX912

**19" XTREME LCD MONITOR
WITH 5MS ULTRA-FAST RESPONSE TIME**

It's not just a multimedia LCD. It's a ViewSonic.



ELEGANT DESIGN WITH MULTIMEDIA FEATURES

- > **ClearMotiv™ 5ms video response time**
Ultra-fast 5ms video response delivers broadcast-quality full motion video.
- > **Dynamic Structure™ technology**
Innovative liquid crystal composition and pixel matrix accelerates video response for seamless video and intense graphics.
- > **OptiSync® digital/analogue inputs expand your connectivity**
Multi-mode input technology supports both digital (DVI) and analogue (VGA) signals for ultimate compatibility and configuration flexibility.
- > **Multimedia enhanced**
Save workspace and enjoy rich stereo sound with invisible built-in stereo speakers.
- > **Stylish slim-bezel design**
Slim-bezel design ensures that the VX912 looks good no matter if it's on or off.
- > **Ultra-high brightness and contrast**
300 cd/m² brightness and 700:1 contrast levels deliver rich, crisp, detailed images.
- > **Full 19" viewable with 1280 x 1024 resolution**
- > **PC and Mac® compatible**



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic® 
the choice of professionals

VX912

19" XTREME LCD MONITOR WITH 5MS ULTRA-FAST RESPONSE TIME



| | | |
|-----------------------------|--------------------|---|
| LCD | Type | 19" TN colour TFT active matrix SXGA LCD |
| | Display Area | 37.6cm horizontal x 30.1cm vertical, 48.3cm diagonal |
| | Pixel Pitch | 0.294mm |
| | Optimum Resolution | 1280 x 1024 |
| | Pixel Clock | 135MHz |
| | Contrast Ratio | 700:1 (typ.) |
| | Viewing Angle | 150° horizontal, 135° vertical (at 10:1) 170° horizontal, 155° vertical (at 5:1) |
| | Response Time | 5ms (off-on-off) (typ.) |
| | Colour Support | 16.2M colours (6-bit+2-bit FRC) |
| | Brightness | 300cd/m ² |
| Panel Surface | Anti-glare (3H) | |
| VIDEO INPUT | Analogue | RGB analogue (0.7 Vp-p, 75 ohm) |
| | Digital | DVI-D (TMDS, 100 ohm) |
| | Frequency | F _H : 30 – 82kHz, F _V : 50 – 85Hz |
| | Synchronisation | H/V separate (TTL), composite, sync on green |
| COMPATIBILITY | PC | VGA up to 1280 x 1024 non-interlaced (max. 75Hz) |
| | Mac ^{®1} | Power Mac™ up to 1280 x 1024 non-interlaced (max. 75Hz) |
| CONNECTOR | Analogue | 15-pin mini D-Sub (detachable cable) |
| | Digital | 24-pin DVI-D (detachable cable) |
| | Audio | 3.5mm stereo audio line-in |
| | Power | 3-pin (CEE22) |
| AUDIO | Speakers | 2 x 1 watt |
| POWER | Voltage | AC 100 – 240V, 50/60Hz (auto switch), internal power supply |
| | Consumption | 35 watt (typ.), <1 watt in power save mode |
| ERGONOMICS | Tilt | Down 5°, Up 20° |
| CONTROLS | Basic | Power on/off, menu [1], up, down, select [2] |
| | OSD | Auto image adjust, contrast, brightness, input select (D-sub, DVI-D), colour adjust (sRGB, 9300K, 6500K, 5400K, user RGB), information (resolution, H/V frequency, pixel clock, model number, serial number, website), manual image adjust (H/V position, H size, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), OSD/power lock, memory recall |
| OPERATING CONDITIONS | Temperature | 0°C to 40°C |
| | Humidity | 10% to 90% (non-condensation) |
| DIMENSIONS | (W x H x D mm) | 431 x 468 x 201 (with stand) 431 x 370 x 66 (without stand) |
| | WEIGHT | Net |
| REGULATIONS | | TCO'99, NEMKO/GS ² , NEMKO/ERGO ³ , CE, CB, UL, cUL, FCC-B, ENERGY, NOM, ISO13406-2 (pixel failure class II), GOST-R (+Hygienic), (SASO), PCBC, VCCI, BSMI, CCC, (PSB), (C-TICK), Argentina-S, PSE, Green Mark |
| POWER MANAGEMENT | | Meets TCO'99 and ENERGY standards |
| SECURITY | | Kensington® security port |
| WALL MOUNT | | VESA FDMI 100mm x 100mm |
| PACKAGE CONTENT | | LCD Monitor, power cable, 15-pin VGA video cable, audio cable, Quick Start Guide, ViewSonic Wizard CD-ROM (User Guide/drivers) |
| WARRANTY | | Please see: www.viewsoniceurope.com/UK/Support/warranty.htm |



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Europe Limited/UK

ViewSonic House
Fleming Way, Crawley
West Sussex, RH10 9GA
United Kingdom

Tel: +44 (0) 12 93 64 39 00
Fax: +44 (0) 12 93 64 39 10

ViewSonic Germany

Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany

Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France

Parc des Barbannières
1 allée des Bas Tilliers
92230 Gennevilliers
France

Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation

381 Brea Canyon Road
Walnut
California 91789-0708
USA

Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Belux

ViewSonic Denmark

ViewSonic Finland

ViewSonic Italy

ViewSonic MEA

ViewSonic Netherlands

ViewSonic Norway

ViewSonic Spain

ViewSonic Sweden

Tel: +32 (0)56 85 26 27
Tel: +45 70 22 11 71
Tel: +358 (0)9 5406 4070
Tel: +39 02 73 95 50 22
Tel: +971 (0) 4 88 11 871
Tel: +31 (0)20 491 9254
Tel: +47 (0) 22 88 17 60
Tel: +34 (0) 91 63 05 339
Tel: +46 (0) 8 50 71 30 00

¹ May require optional Mac adapter. ² Equivalent to TÜV/GS. ³ Equivalent to TÜV/ERGO.

Copyright © 2006, ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. VS VX912-09/06-UK