

## Ultra-stylish large wide-screen monitor

With the VX2235wm 22" wide-screen LCD, ViewSonic sets new standards in style and video performance. See the difference with movies in 16:10 wide-screen format for the ultimate viewing experience. Immerse yourself in games with the breathtaking large screen size. Enjoy high brightness and contrast levels and wide viewing angles which generate bright, vivid, detailed images. And even fast-action movies and games are free from blurs or ghosting thanks to a super-fast response time of 5ms. Analogue and Digital inputs offer the maximum in connectivity options; built-in multimedia speakers offer the greatest ease of use. Furthermore, with its eye-catching slim bezel styling, the VX2235wm is a design statement that will grace any home or office.

**IT'S NOT JUST ANOTHER WIDE-SCREEN LCD. IT'S A VIEWSONIC.**

# VX2235wm

**22" WIDE-SCREEN  
LCD MONITOR  
WITH 5MS CLEARMOTIV™  
RESPONSE TIME**



### SUPERIOR PERFORMANCE ELEGANTLY STYLED

- > **Award Winning Performance and response times**  
See the difference with ViewSonic's award-winning screen performance. 280cd/m<sup>2</sup> brightness levels and 700:1 contrast ratio deliver rich, crisp, detailed images. 5ms response time provides fluid, high-quality video performance. Up to 170° viewing angles ensure enhanced image performance from any angle.
- > **Wide-Screen Performance for Movies**  
Experience movies in wide-screen format – the 16:10 aspect ratio delivers the ultimate in video performance.
- > **Wide-Screen Performance for Entertainment**  
Immerse yourself in full wide-screen views for intense gaming action.
- > **Wide-Screen Performance for Business**  
Improve productivity and performance with wide-screen format. Display multiple pages, larger spreadsheets and more on a single screen without need to swap between documents.
- > **Multimedia Versatility**  
For games, movies and even office applications, the built-in stereo speakers deliver high quality audio.
- > **Analogue and Digital Inputs**  
Enjoy maximum connectivity and maximum video performance with both analogue VGA and digital DVI connections.
- > **Full 22" viewable display with 1680 x 1050 resolution.**



**VIEWSONIC**  
PRODUCTS, PROGRAMS,  
AND SERVICES

**ViewSonic**   
*the choice of professionals*

# VX2235wm

## 22" WIDE-SCREEN LCD MONITOR WITH 5MS CLERMOTIV™ RESPONSE TIME



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

<b>LCD</b>	Type	22" Wide TN colour TFT active matrix WSXGA+ LCD
	Display Area	47.4cm horizontal x 29.6cm vertical; 55.9cm diagonal
	Pixel Pitch	0.282mm
	Optimum Resolution	1680 x 1050@60Hz
	Pixel Clock	150MHz
	Contrast Ratio	700:1 (typ.)
	Viewing Angle	150° horizontal, 140° vertical (at 10:1), 170° horizontal, 160° vertical (at 5:1)
	Response Time	5ms (off-on-off) (typ.)
	Colour Support	16.2M colours (6-bit+2-bit FRC)
	Light Source	Long life, 40000 hrs. (min.)
	Brightness	280cd/m <sup>2</sup>
	Panel Surface	Anti-glare (3H)
<b>VIDEO INPUT</b>	Analogue	RGB analogue (0.7 Vp-p, 75 ohm)
	Digital	DVI-D (TMDS, 100 ohm)
	Frequency	Fh: 30 – 82kHz, Fv: 50 – 85Hz
	Synchronisation	H/V separate (TTL), composite, sync on green
<b>COMPATIBILITY</b>	PC	VGA up to 1680 x 1050 non-interlaced
	Mac <sup>®1</sup>	Power Mac™ up to 1680 x 1050 non-interlaced
<b>CONNECTOR</b>	Analogue	15-pin mini D-Sub (detachable cable)
	Digital	24-pin DVI-D (detachable cable)
	Audio	3.5mm stereo audio line-in
	Power	3-pin AC plug (CEE22)
<b>AUDIO</b>	Speakers	2 x 2.5 watt integrated stereo speakers
<b>POWER</b>	Voltage	AC 100 – 240V, 50/60Hz (auto switch), internal power supply
	Consumption	48 watt (typ.), <1 watt in power save mode
<b>ERGONOMICS</b>	Tilt	Down 5°, Up 20°
<b>CONTROLS</b>	Basic	Power, menu [1], up, down, select [2]
	OSD	Auto image adjust, contrast, brightness, input select (D-sub, DVI-D), ViewMatch® colour adjust (sRGB, 9300K, 7500K, 6500K, 5400K, user RGB), information (resolution, H/V frequency, pixel clock, model number, serial number, website), manual image adjust (H/V position, H size, fine tune, sharpness, Opticolour [standard, text, cinema, game, portrait, scenery, vivid], Opticolour skin tone [nature, reddish, yellowish]), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), OSD/power lock, memory recall
<b>OPERATING CONDITIONS</b>	Temperature	5°C – 35°C
	Humidity	20% – 80% (non-condensation)
<b>DIMENSIONS</b>	(W x H x D mm)	524 x 482 x 244 (physical with stand) 524 x 389 x 58 (physical without stand) 575 x 550 x 522 (packaging)
<b>WEIGHT</b>	Net	6.0kg (with stand) 4.8kg (without stand)
	Gross	7.5kg
<b>REGULATIONS</b>		CB, CE, TÜV/ERGO, CE, GOST-R+Hygienic, SASO, ENERGY, MPR II, WEEE, RoHS
<b>POWER MANAGEMENT</b>		Meets MPR II and ENERGY standards
<b>SECURITY</b>		Kensington® security port
<b>WALL MOUNT</b>		VESA® FDMI 100mm x 100mm
<b>PACKAGE CONTENT</b>		LCD Monitor, power cable, 15-pin VGA video cable, DVI cable, Quick Start Guide, audio cable, ViewSonic Wizard CD-ROM (User Guide/drivers) (multi-language)
<b>WARRANTY</b>		Please see: <a href="http://www.viewsoniceurope.com/UK/Support/warranty.htm">www.viewsoniceurope.com/UK/Support/warranty.htm</a>

### ViewSonic Europe Limited/UK

ViewSonic House  
Fleming Way, Crawley  
West Sussex, RH10 9GA  
United Kingdom

Tel: +44 (0) 12 93 64 39 00  
Fax: +44 (0) 12 93 64 39 10

### ViewSonic Germany

Hanns-Martin-Schleyer-Straße 18A  
47877 Willich  
Germany

Tel: +49 (0) 21 54 91 88 0  
Fax: +49 (0) 21 54 91 88 10

### ViewSonic France

Parc des Barbanniers  
1 allée des Bas Tilliers  
92230 Gennevilliers  
France

Tel: +33 (0) 1 41 47 49 00  
Fax: +33 (0) 1 41 47 49 10

### ViewSonic Corporation

381 Brea Canyon Road  
Walnut  
California 91789-0708  
USA

Tel: +1 909 869 7976  
Fax: +1 909 869 7958

### ViewSonic Belux

### ViewSonic Denmark

### ViewSonic Finland

### ViewSonic Italy

### ViewSonic MEA

### ViewSonic Netherlands

### ViewSonic Norway

### ViewSonic Spain

### ViewSonic Sweden

Tel: +32 (0)56 85 26 27  
Tel: +45 70 22 11 71  
Tel: +358 (0)9 5406 4070  
Tel: +39 02 73 95 50 22  
Tel: +971 (0) 4 88 11 871  
Tel: +31 (0)20 491 9254  
Tel: +47 (0) 22 88 17 60  
Tel: +34 (0) 91 63 05 339  
Tel: +46 (0) 8 50 71 30 00

<sup>1</sup> May require optional Mac adapter.