



DES-1008FX 100 Fast Ethernet Switch User's Guide

(Draft 2: 01/07/99)

Rev. 01 (9, 1997)

6xxxxxxx.01

Printed In Taiwan



RECYCLABLE

WARRANTIES EXCLUSIVE

IF THE D-LINK PRODUCT DOES NOT OPERATE AS WARRANTED ABOVE, THE CUSTOMER'S SOLE REMEDY SHALL BE, AT D-LINK'S OPTION, REPAIR OR REPLACEMENT. THE FOREGOING WARRANTIES AND REMEDIES ARE EXCLUSIVE AND ARE IN LIEU OF ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, EITHER IN FACT OR BY OPERATION OF LAW, STATUTORY OR OTHERWISE, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. D-LINK NEITHER ASSUMES NOR AUTHORIZES ANY OTHER PERSON TO ASSUME FOR IT ANY OTHER LIABILITY IN CONNECTION WITH THE SALE, INSTALLATION MAINTENANCE OR USE OF D-LINK'S PRODUCTS. D-LINK SHALL NOT BE LIABLE UNDER THIS WARRANTY IF ITS TESTING AND EXAMINATION DISCLOSE THAT THE ALLEGED DEFECT IN THE PRODUCT DOES NOT EXIST OR WAS CAUSED BY THE CUSTOMER'S OR ANY THIRD PERSON'S MISUSE, NEGLIGENCE, IMPROPER INSTALLATION OR TESTING, UNAUTHORIZED ATTEMPTS TO REPAIR, OR ANY OTHER CAUSE BEYOND THE RANGE OF THE INTENDED USE, OR BY ACCIDENT, FIRE, LIGHTNING OR OTHER HAZARD.

LIMITATION OF LIABILITY

IN NO EVENT WILL D-LINK BE LIABLE FOR ANY DAMAGES, INCLUDING LOSS OF DATA, LOSS OF PROFITS, COST OF COVER OR OTHER INCIDENTAL, CONSEQUENTIAL OR INDIRECT DAMAGES ARISING OUT OF THE INSTALLATION, MAINTENANCE, USE, PERFORMANCE, FAILURE OR INTERRUPTION OF A D-LINK PRODUCT, HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY. THIS LIMITATION WILL APPLY EVEN IF D-LINK HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE. IF YOU PURCHASED A D-LINK PRODUCT IN THE UNITED STATES, SOME STATES DO NOT ALLOW THE LIMITATION OR EXCLUSION OF LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU..

Limited Warranty

Hardware:

D-Link warrants its hardware products to be free from defects in workmanship and materials, under normal use and service, for the following lengths of time from the date of purchase from D-Link or its Authorized Reseller:

| <u>Product Type</u> | <u>Warranty Period</u> |
|--|------------------------|
| Network adapters | Lifetime |
| Unmanaged Ethernet Switch | Lifetime |
| Managed Ethernet Switch | 3 years |
| Unmanaged and managed hubs (10Mbps) | Lifetime * |
| Unmanaged and managed hubs (100Mbps) | One year |
| Repeaters, MAUs , transceivers, media converters | One year |
| Concentrators | One year |
| Internetworking products | One year |
| * Power supply and fans in these devices | One year |
| Other hardware products | One year |
| Spare parts and spare kits | 90 days |

If a product does not operate as warranted during the applicable warranty period, D-Link shall, at its option and expense, (1) repair the defective product or part, (2) deliver to Customer an equivalent product or part to replace the defective item. All products that are replaced will become the property of D-Link. Replacement products may be new or reconditioned. Any replaced or repaired product or part has a ninety (90) day warranty or the remainder of the initial warranty period, whichever is longer.

D-Link shall not be responsible for any software, firmware, information, or memory data of Customer contained in, stored on, or integrated with any products returned to D-Link pursuant to any warranty. All products with lifetime warranty have a standard five-year warranty. To qualify for lifetime warranty, the enclosed Product Registration Card must be completed and returned to D-Link within ninety (90) days of purchase.

Warranty service may be obtained by contacting a D-Link office within the applicable warranty period for a Return Material Authorization (RMA) number. If a Registration Card has not been previously sent, proof of purchase, such as a copy of the dated purchase invoice, must be provided. Once an RMA number is issued, the defective product must be shipped back to D-Link prepaid, insured and wrapped in the original or similar shipping package to ensure that it will not be damaged during shipment. When returning the defective product to D-Link for service, the RMA number must be marked on the outside of the shipping package. Any product returned without an RMA number shall be rejected and sent back to the Customer, and D-Link reserves the

right to have Customer bear the cost of sending back such products. A service charge may or may not be levied to Customer by D-Link. To find out if a service charge is levied or not, and the charged amount, read the RMA that is returned to Customer, or ask the D-Link office when an RMA is requested. **Software:** D-Link warrants that the software programs licensed from it will perform in substantial conformance to the applicable published program specifications for a period of ninety (90) days from the date of purchase from D-Link or its Authorized Reseller. D-Link warrants the magnetic media containing software against failure during the warranty period. No updates are provided. D-Link's sole obligation hereunder shall be to replace any defective software products with products which substantially conform to D-Link's applicable published specifications. Customer assumes responsibility for the selection of the appropriate applications program and associated reference materials. D-Link makes no warranty that its software products will work in combination with any hardware or applications software products provided by third party, that the operation of the software products will be uninterrupted or error free, or that all defects in the software product will be corrected. For any third party products listed in the D-Link software product documentation or specifications as being compatible, D-Link will make reasonable efforts to provide compatibility, except where the non-compatibility is caused by "bug" or defect in the third party's product. Warranty service for software products may be obtained by contacting a D-Link office within the warranty period. Where no Product Registration Card has been sent by Customer, proof of purchase, such as a copy of the dated purchased invoice, must be provided.

D-Link Offices to Contact for Warranty Service:

To mail your Registration Card, or to obtain an RMA number or warranty service, see the following address:

In North, Central, and South America:

D-Link Systems Inc.
5 Musick, Irvine CA 92618
Tel. (1)714-455-1688 Fax (1)714-455-1261

In Europe and Israel:

D-Link Europe
Denmark House, Staples Corner, The Broadway, London NW9 7BW, U.K.
Tel. (44)181-203-9900 Fax (44)181-203-6915

In the Middle East (except Israel), Asia, Oceania and Africa:

D-Link Corporation
No. 233-2, 2nd F. Pao Chiao Road, Hsin Tien Taipei, Taiwan
TEL. (886)2-916-1600

Trademarks

Copyright ©1997 D-Link Corporation.
D-Link © is a registered trademark of D-Link Corporation/D-Link Systems, Inc.

All rights reserved, contents may be revised without prior notice.
FlexSWITCH™ is a trademark of D-Link Systems, Inc.
Ethernet is a trademark of Xerox Corporation.
Microsoft Windows is a trademark of Microsoft Corporation.
VT100 is a trademark of Digital Equipment Corporation.
All other trademarks belong to their respective proprietors.

Copyright Statement

No part of this publication may be reproduced in any form or by any means or used to make any derivative such as translation, transformation, or adaptation without permission from D-Link Corporation/D-Link Systems Inc., as stipulated by the United States Copyright Act of 1976.

FCC Warning

This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with this user's guide, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense.

CE Mark Warning

This is a Class A product. In a domestic environment, this product may cause radio interference in which case the user may be required to take adequate measures.

注意

この装置は、情報処理装置等電波障害自主規制協議会 (VCCID) の基準に基づく第一種情報技術装置です。この装置を家庭環境で使用すると電波妨害を引き起こすことがあります。この場合には使用者が適切な対策を講ずるよう要求されることがあります。

Wichtige Sicherheitshinweise

Bitte lesen Sie sich diese Hinweise sorgfältig durch.

Heben Sie diese Anleitung für den spätem Gebrauch auf.

Vor jedem Reinigen ist das Gerät vom Stromnetz zu trennen. Verwenden Sie keine Flüssig- oder Aerosolreiniger. Am besten dient ein angefeuchtetes Tuch zur Reinigung.

Um eine Beschädigung des Gerätes zu vermeiden sollten Sie nur Zubehörteile verwenden, die vom Hersteller zugelassen sind.

Das Gerät ist vor Feuchtigkeit zu schützen.

Bei der Aufstellung des Gerätes ist auf sichern Stand zu achten. Ein Kippen oder Fallen könnte Verletzungen hervorrufen. Verwenden Sie nur sichere Standorte und beachten Sie die Aufstellhinweise des Herstellers.

Die Belüftungsöffnungen dienen zur Luftzirkulation die das Gerät vor Überhitzung schützt. Sorgen Sie dafür, daß diese Öffnungen nicht abgedeckt werden.

Beachten Sie beim Anschluß an das Stromnetz die Anschlußwerte.

Die Netzanschlußsteckdose muß aus Gründen der elektrischen Sicherheit einen Schutzleiterkontakt haben.

Verlegen Sie die Netzanschlußleitung so, daß niemand darüber fallen kann. Es sollte auch nichts auf der Leitung abgestellt werden.

Alle Hinweise und Warnungen die sich am Geräten befinden sind zu beachten.

Wird das Gerät über einen längeren Zeitraum nicht benutzt, sollten Sie es vom Stromnetz trennen. Somit wird im Falle einer Überspannung eine Beschädigung vermieden.

Durch die Lüftungsöffnungen dürfen niemals Gegenstände oder Flüssigkeiten in das Gerät gelangen. Dies könnte einen Brand bzw. Elektrischen Schlag auslösen.

Öffnen Sie niemals das Gerät. Das Gerät darf aus Gründen der elektrischen Sicherheit nur von autorisiertem Servicepersonal geöffnet werden.

Wenn folgende Situationen auftreten ist das Gerät vom Stromnetz zu trennen und von einer qualifizierten Servicestelle zu überprüfen:

Netzkabel oder Netzstecker sind beschädigt.

Flüssigkeit ist in das Gerät eingedrungen.

Das Gerät war Feuchtigkeit ausgesetzt.

Wenn das Gerät nicht der Bedienungsanleitung entsprechend funktioniert oder Sie mit Hilfe dieser Anleitung keine Verbesserung erzielen.

Das Gerät ist gefallen und/oder das Gehäuse ist beschädigt.

Wenn das Gerät deutliche Anzeichen eines Defektes aufweist.

Bei Reparaturen dürfen nur Originalersatzteile bzw. den Originalteilen entsprechende Teile verwendet werden.

Der Einsatz von ungeeigneten Ersatzteilen kann eine weitere Beschädigung hervorrufen.

Wenden Sie sich mit allen Fragen die Service und Reparatur betreffen an Ihren Servicepartner. Somit stellen Sie die Betriebssicherheit des Gerätes sicher.

TABLE OF CONTENTS

| | |
|--|------------|
| ABOUT THIS GUIDE | III |
| TERMS | III |
| OVERVIEW OF THIS USER'S GUIDE | III |
| INTRODUCTION | 1 |
| FAST ETHERNET TECHNOLOGY | 1 |
| SWITCHING TECHNOLOGY | 2 |
| FEATURES | 3 |
| <i>Ports</i> | 3 |
| <i>Performance features</i> | 3 |
| UNPACKING AND SETUP | 5 |
| UNPACKING | 5 |
| SETUP | 6 |
| DESKTOP OR SHELF INSTALLATION | 6 |
| RACK INSTALLATION | 7 |
| POWER ON | 8 |
| <i>Power Failure</i> | 9 |
| IDENTIFYING EXTERNAL COMPONENTS | 10 |
| FRONT PANEL | 10 |
| REAR PANEL | 11 |
| LED INDICATORS | 12 |
| CONNECTING THE SWITCH | 14 |
| PC TO SWITCH | 14 |
| HUB TO SWITCH | 15 |

| | |
|--|-----------|
| <i>100Base-FX Hub</i> | 15 |
| SWITCH TO SWITCH..... | 16 |
| CONFIGURING THE SWITCHES | 17 |
| SUMMARY..... | 17 |
| FIBER CONNECTOR SC PIN SPECIFICATIONS | 21 |
| INDEX | 23 |

ABOUT THIS GUIDE

This User's guide tells you how to install your DES-1008FX, how to connect it to your Fast Ethernet network using fiber cable, and how to set its configuration using the built-in back panel DIP switch.

Terms

For simplicity, this documentation uses the terms “Switch” (first letter upper case) to refer to the DES-1008FX 100 Fast Ethernet Switch, and “switch” (first letter lower case) to refer to all Ethernet switches, including the DES-1008FX.

Overview of this User's Guide

- ◆ Chapter 1, *Introduction*. Describes the switch and its features.
- ◆ Chapter 2, *Unpacking and Setup*. Helps you get started with the basic installation of the switch.
- ◆ Chapter 3, *Identifying External Components*. Describes the front panel, rear panel and LED indicators of the switch.
- ◆ Chapter 4, *Connecting the Switch*. Tells how you can connect the DES-1008FX to your Fast Ethernet network.

- ◆ Chapter 5, *Configuring the Switch*. Tells how to use the built-in back panel DIP switch to set switch parameters for full or half duplex.
- ◆ Appendix A, *Technical Specifications*. Lists the technical specifications of the DES-1008FX.
- ◆ Appendix B, *Fiber Connector SC Pin Specifications*. Shows the details and pin assignments for the Fiber Module receptacle/ connector.

1

INTRODUCTION

This section describes the features of the DES-1008FX, as well as giving some background information about Fast Ethernet switching technology.

Fast Ethernet Technology

The growing importance of LAN s and the increasing complexity of desktop computing applications are fueling the need for high performance networks. A number of high-speed LAN technologies are proposed to provide greater bandwidth and improve client/server response times. Among them, Fast Ethernet, or 100Base-TX or 100Base-FX, provides a non-disruptive, smooth evolution from the current 10Base-T technology. The non-disruptive and smooth evolution nature, and the dominating potential market base, virtually guarantee cost effective and high performance Fast Ethernet solutions in the years to come.

100Mbps Fast Ethernet is a new standard specified by the IEEE 802.3 LAN committee. It is an extension of the 10Mbps Ethernet standard with the ability to transmit and receive data at 100Mbps, while maintaining the CSMA/CD Ethernet protocol. Since the 100Mbps Fast Ethernet is compatible with all other 10Mbps Ethernet environments, it provides a straightforward upgrade and

takes advantage of the company's existing investment in hardware, software, and personnel training.

Switching Technology

Another approach to pushing beyond the limits of Ethernet technology is the development of Switching technology. A switch bridges Ethernet packets at the MAC address level of the Ethernet protocol transmitting among connected Ethernet or fast Ethernet LAN segments.

Switching is a cost-effective way of increasing the total network capacity available to users on a local area network. A switch increases capacity and decreases network loading by making it possible for a local area network to be divided into different *segments* which don't compete with each other for network transmission capacity, giving a decreased load on each.

The switch acts as a high-speed selective bridge between the individual segments. Traffic that needs to go from one segment to another is automatically forwarded by the switch, without interfering with any other segments. This allows the total network capacity to be multiplied, while still maintaining the same network cabling and adapter cards.

For Fast Ethernet networks, a switch is an effective way of eliminating problems of chaining hubs beyond the "two-repeater limit." A switch can be used to split parts of the network into different collision domains, making it possible to expand your Fast Ethernet network beyond the 205-meter network diameter limit for 100BASE-FX networks. Switches supporting both traditional 10Mbps Ethernet and 100Mbps Fast Ethernet are also ideal for bridging between existing 10Mbps networks and new 100Mbps networks.

Switching LAN technology is a marked improvement over the previous generation of network bridges, which were characterized by higher latencies. Routers have also been used to segment local area networks, but the cost of a router and the setup and maintenance required make routers relatively impractical. Today's switches are an ideal solution to most kinds of local area network congestion problems.

Features

The DES-1008FX Switch was designed for easy installation and high performance in an environment where traffic on the network and the number of users increase continuously.

The DES-1008FX Switch features:

Ports

- ◆ 8 high performance 100BaseFX ports all operating at 100 Mbps for connection to workstation, servers and hubs. All ports can be selected to perform half-duplex or full duplex connections.
- ◆ Select any of 8 ports for uplink/ MDI-X (media dependent interface) port for uplink to another switch, hub or repeater.

Performance features

- ◆ Store and forward switching scheme capability to support rate adaptation and protocol conversion.

- ◆ Full and Half-duplex at 100Mbps to allow two communicating stations to transmit and receive at the same time.
- ◆ Data forwarding rate 148,800 pps per port at 100% of fiber-speed.
- ◆ Data filtering rate eliminates all error packets, runts, etc. at 148,800 pps per port at 100% of fiber-speed.
- ◆ 8K active MAC address entry table per device with self-learning and table aging.
- ◆ 2 MB packet buffer per port.
- ◆ Supports broadcast storm rate filtering.

2

UNPACKING AND SETUP

This chapter provides unpacking and setup information for the Switch.

Unpacking

Open the shipping carton of the Switch and carefully unpack its contents. The carton should contain the following items:

- ◆ One DES-1008FX 100Mbps Fast Ethernet Switch
- ◆ Four rubber feet with adhesive backing
- ◆ 1 AC power cord
- ◆ This user's guide with Registration Card

If any item is found missing or damaged, please contact your local D-Link Reseller for replacement.

Setup

The setup of the Switch can be performed using the following steps:

- ◆ The surface must support at least 3 Kg.
- ◆ The power outlet should be within 1.82 meters (6 feet) of the device.
- ◆ Visually inspect the power cord and see that it is secured fully to the AC power connector.
- ◆ Make sure that there is proper heat dissipation from and adequate ventilation around the Switch. Do not place heavy objects on the Switch.

Desktop or Shelf Installation

When installing the Switch on a desktop or shelf, the rubber feet included with the device must be first attached. Attach these cushioning feet on the bottom at each corner of the device. Allow enough ventilation space between the device and the objects around it.




Figure 1. DES-1008FX Fast Ethernet Switch installed on a Desktop or Shelf

Rack Installation

The DES-1008FX can be mounted in an EIA standard size, 19-inch rack, which can be placed in a wiring closet with other equipment. To install, attach the mounting brackets on the switch's front panel (one on each side) and secure them with the screws provided.



Figure 2A. Attaching the mounting brackets to the DES-1008FX 100Mbps Fast Ethernet Switch

Then, use the screws provided with the equipment rack to mount the Switch in the rack.




Figure 2B. Installing the DES-1008FX 100Mbps Fast Ethernet Switch in an equipment rack

Power on

The DES-1008FX Switch can be used with AC power sources 100 - 240 VAC, 50 - 60 Hz. The power switch is located at the rear of the unit adjacent to the AC power connector and the system fan. The Switch's power supply will adjust to the local power source automatically and may be turned on without having any or all LAN segment cables connected.

After the power switch is turned on, the LED indicators should respond as follows:

- ◆ The power LED indicator will turn on and remain *ON*. .

Power Failure

As a precaution, the Switch should be turned **OFF** in case of power failure. When power is resumed, turn the Switch ON. At all times, avoid leaving the Switch ON after the occurrence of a power failure.

3

IDENTIFYING EXTERNAL COMPONENTS

This chapter describes the front panel, rear panel and LED indicators of the Switch

Front Panel

The front panel of the Switch consists of 8 (100 Mbps) 100BaseFX ports and LED indicators.



Figure 3. Front panel view of the DES-1008FX Switch

- ◆ 8 high performance 100BaseFX ports all operating at 100 Mbps for connection to servers and hubs. All ports can be set to perform 100Mbps half-duplex or full duplex connections.
- ◆ Select any of 8 ports for uplink to another switch, hub or repeater.
- ◆ Comprehensive LED indicators that display the conditions of the Switch and status of the network. A description of these LED indicators follows (see *LED Indicators*).

Rear Panel

The rear panel of the Switch consists of a power switch, an AC power connector, an Half/Full Duplex DIP switch and a system fan. The following shows the rear panel of the Switch.



Figure 4. Rear panel view of the DES-1008FX

- ◆ **System Fans.** These fans are used to circulate air inside the Switch and also to dissipate heat. The sides of the system also provide heat vents to serve the same purpose. Do not block these openings, and leave adequate space at the rear and sides of the Switch for proper ventilation. Be reminded that without proper heat dissipation and air

circulation, system components might overheat, which could lead to system failure.

- ◆ **Duplex Mode Switch.** This bank of eight switches changes the ports between full and Half-Duplex modes. The switches are ordered reverse to the front panel ports. Example front port 1 is switch 8. Half-Duplex is "DOWN" or "ON". Full-Duplex is "UP" or "OFF". Default settings for the DES-1008FX are all "DOWN/ON" at Half-Duplex.
- ◆ **AC Power Connector.** This is a three-pronged connector that supports the power cord. Plug in the female connector of the provided power cord into this connector, and the male into a power outlet. Supported input voltages range from 100 ~ 240 VAC at 50 ~ 60 Hz.
- ◆ **Power Switch.** This turns the Switch on and off. To turn on the system, press the switch to the "1" position; to turn off, press the switch to the "0" position.

LED Indicators

The LED indicators of the Switch include Power, Link, Act, FDX and Col. The following shows the LED indicators for the Switch along with an explanation of each indicator.




Figure 5. The DES-1008FX Switch LED indicators

- ◆ **Power.** This indicator operates when the Switch is turned ON (**green**). If this indicator is not lit, check the AC power connector to assure proper insertion of the power cord and the power switch is turned ON.
- ◆ **Link** These LED indicators are illuminated (**green**) when a 100 Mbps device is connected to any of the 8 ports or uplink port.
- ◆ **Act.** The LED indicators turn on (**green**) whenever there is reception or transmission (i.e. Activity--Act) of data occurring at a port.
- ◆ **FDX** This LED indicator is **green** when a respective port is in full duplex (FDX) mode.
- ◆ **Col.** It blinks **yellow** when collisions are occurring on the respective port.

CONNECTING THE SWITCH

This chapter describes how to connect the DES-1008FX to your Fast Ethernet network.

PC to Switch

A PC can be connected to the Switch via a two-string fiber straight cable. The PC (equipped with a 100 Mbps SC jack) should be connected to any of the eight ports (1x - 8x) of the DES-1008FX.

The LED indicators for PC connection are dependent on the LAN card capabilities. If LED indicators are not illuminated after making a proper connection, check the PC's LAN card, the cable, Switch conditions and connections.

NOTE: If your SC connectors are not locked together the TX and RX on the PC's side, the cable connectors at the switch must be reversed to RX and TX of the Switch. This allows a TX from the card to enter into the RX of the switch. Locked (paired) SC connectors should be manufactured in this manner.

The following are LED indicator possibilities for a PC to Switch connection:

1. The Link LED indicator comes ON upon hookup.
2. The Act. LED indicator illuminates if data upon hookup.
3. The FDX LED indicator depends upon LAN card capabilities and DIP switch setting at DES-1008FX back panel.
4. The Col. LED indicator depends upon communication activity.

Hub to Switch

A hub (100Base-FX) can be connected to the Switch via a two-string fiber crossover cable.

NOTE: If your SC connectors are not locked together the TX and RX on the PC's side, the cable connectors at the switch must be reversed to RX and TX of the Switch. This allows a TX from the card to enter into the RX of the switch. Locked (paired) SC connectors should be manufactured in this manner.

100Base-FX Hub

A traditional repeater/hub can only accomplish Half-Duplex setting. Set the DES-1008FX Duplex Mode switches for Half-Duplex of the ports that are hook to these hubs.

For a 100Base-FX hub, the Switch's LED indicators should illuminate the following:

- ◆ The Link LED indicator comes ON upon hookup.
- ◆ The Act. LED indicator illuminates if data upon hookup.
- ◆ The FDX LED indicator should be off.

- ◆ The Col. LED indicator depends upon communication activity.

Switch to Switch

A 100Base-FX compatible switch can be connected to the Switch via a two-string fiber crossover cable.

Switch the Duplex mode switches to the appropriate selections to get the maximum bandwidth. Consult the other switches manual for the proper setting of Duplex Modes. The DES-1008FX Duplex Mode switches can be found on the back of the unit. "DOWN/ON" is Half-Duplex and "UP/OFF" is Full-Duplex.

NOTE: If your SC connectors are not locked together the TX and RX on the PC's side, the cable connectors at the switch must be reversed to RX and TX of the Switch. This allows a TX from the card to enter into the RX of the switch. Locked (paired) SC connectors should be manufactured in this manner.

The "uplinked" Switch LED indicators for the respective connected ports are as follows:

- ◆ The Link LED indicator comes ON upon hookup.
- ◆ The Act. LED indicator illuminates if data upon hookup.
- ◆ The FDX LED indicator depends upon the "uplinked" switch's capabilities and Duplex Mode switch setting at DES-1008FX back panel.
- ◆ The Col. LED indicator depends upon communication activity.

5

CONFIGURING THE SWITCHES

Summary

The DES-1008FX is a Auto-Learning unintelligent 100BaseFX Fast Ethernet Switch.

The only configuration that can be done is the Duplex Mode. This bank of eight switches changes the ports between full and half duplex modes. The switches are ordered reverse to the front panel ports. Example front port 1 is switch 8. Half-Duplex is "DOWN" or "ON". Full-Duplex is "UP" or "OFF". Default settings for the DES-1008FX are all "DOWN/ON" at Half-Duplex.

Any further configuration is not necessary for the DES-1008FX.



TECHNICAL SPECIFICATIONS

| General | |
|---------------------|---|
| Standards: | IEEE 802.3u 100 Base-FX Fast Ethernet ANSI/IEEE Std 802.3 IEEE 802.3 Frame types: Transparent IEEE 802.3 MAC layer frame size: 64 - 1518 |
| Protocol: | CSMA/CD |
| Data Transfer Rate: | Fast Ethernet: 100Mbps (half duplex) 200Mbps (full duplex) |
| Topology: | Star |

General

| | |
|------------------|---|
| Network Cables: | 100Base-FX: ISO/IEC 11801 62.5/125-um optical fiber cable (100 m) EIA/TIA-568-A horizontal 62.5/125-um optical fiber cable (100 m) Or ISO/IEC 9314-3 |
| Number of Ports: | 8 x 100 Mbps LAN ports |
| Controller Chips | VLSI |

Physical and Environmental

| | |
|------------------------|---|
| AC inputs: | 100 - 240 VAC, 50/60 Hz (internal universal power supply) |
| Power Consumption: | 40 watts maximum |
| DC fans: | 2 built-in 40x40 mm fan |
| Operating Temperature: | 0 ~ 50 degrees Celsius |
| Storage Temperature: | -40 ~ 70 degree Celsius |
| Humidity: | 5% ~ 95% non-condensing |
| Dimensions: | 324x231x43 mm (1U), 19 inch rack-mount width |
| Weight: | 3 Kg |
| EMI: | FCC Class A, CE Mark Class A, VCCI Class I |
| Safety: | UL (UL 1950), CSA (CSA950), TUV/GS (EN60950) |

Performance



| | |
|-----------------------------------|------------------------------------|
| Transmission Method: | Store-and-forward |
| RAM Buffer: | 8 M bytes per device |
| Filtering Address Table: | 8 K entries per device |
| Packet Filtering/Forwarding Rate: | 148,800 pps per port (for 100Mbps) |
| MAC Address Learning: | Automatic update Max age: fixed |

B

FIBER CONNECTOR SC PIN SPECIFICATIONS

When connecting the DES-1008FX Switch to another switch, a bridge or a hub, a crossover cable is necessary. Please review these products for matching cable pin assignment.

SC fiber connector has push-pull mating mechanism with keyed, molded housing. Connector internal contains a 2.5 mm diameter keyed ferrule. Please refer to EIA/TIA-568A for detail description. The following diagram and tables show the standard fiber connector SC receptacle/connector and their pin assignments for the switch to network adapter card, switch, hub or bridge connection.



The standard fiber connector SC receptacle/connector

| SC Fiber Connector pin assignment | |
|-----------------------------------|----------------------------------|
| Contact | Media Crossover Interface Signal |
| 1 | Tx +(transmit) |
| 2 | Rx - (receive) |
| | |
| | |
| | |
| | |
| | |
| | |

The standard SC Fiber Connector pin assignment

INDEX

I

100 M (speed indicator) 13

A

AC inputs 19

AC Power Connector 12

AC power cord 5

D

Desktop or Shelf Installation 6

Dimensions 19

F

FDX/Col 13

 full duplex 13

Front Panel 10

H

heat dissipation 6

Hub to Switch 15, 16

Humidity 19

I

Identifying External Components
..... 10

L

LAN card 14

LED Indicators 12

M

MAC Address Learning 20

O

Operating Temperature 19

P

PC to Switch 14

Power 12

Power Consumption 19

Power Failure 9

Power on 8

Power Switch 12

R

Rack Installation (DES-1008) 7

RAM Buffer 20

Rear Panel 11

RJ-45 Pin Specification 21

S

Setup 6

Storage Temperature 19

System Fan 11

T

Transmission Methods 20

U

Unpacking 5

V
ventilation6

W
Weight19

Registration Card

Print, type or use block letters.

Your name: Mr./Ms _____
 Organization: _____ Dept. _____
 Your title at organization: _____
 Telephone: _____ Fax: _____
 Organization's full address: _____

 Country: _____
 Date of purchase (Month/Day/Year): _____

| Product Model | Product Serial No. | * Product installed in type of computer (e.g., Compaq 486) | * Product installed in computer serial No. |
|---------------|--------------------|--|--|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

(* Applies to adapters only)

Product was purchased from:
 Reseller's name: _____
 Telephone: _____ Fax: _____
 Reseller's full address: _____

Answers to the following questions help us to support your product:

1. **Where and how will the product primarily be used?**
Home Office Travel Company Business Home Business Personal Use
2. **How many employees work at installation site?**
1 employee 2-9 10-49 50-99 100-499 500-999 1000 or more
3. **What network protocol(s) does your organization use ?**
XNS/IPX TCP/IP DECnet Others _____
4. **What network operating system(s) does your organization use ?**
D-Link LANsmart Novell NetWare NetWare Lite SCO Unix/Xenix PC NFS 3Com 3+Open
Banyan Vines DECnet Pathwork Windows NT Windows NTAS Windows '95
Others _____
5. **What network management program does your organization use ?**
D-View HP OpenView/Windows HP OpenView/Unix SunNet Manager Novell NMS
NetView 6000 Others _____
6. **What network medium/media does your organization use ?**
Fiber-optics Thick coax Ethernet Thin coax Ethernet 10BASE-T UTP/STP
100BASE-TX 100BASE-T4 100VGAnyLAN Others _____
7. **What applications are used on your network?**
Desktop publishing Spreadsheet Word processing CAD/CAM
Database management Accounting Others _____
8. **What category best describes your company?**
Aerospace Engineering Education Finance Hospital Legal Insurance/Real Estate Manufacturing
Retail/Chainstore/Wholesale Government Transportation/Utilities/Communication VAR
System house/company Other _____
9. **Would you recommend your D-Link product to a friend?**
Yes No Don't know yet
10. **Your comments on this product?**

PLEASE
PLACE STAMP
HERE

TO: _____

D-Link®

