



## Access Desktop Applications and the Internet Anywhere Within Your DesXcape Wireless Network!

- **Light and Thin**

The DesXcape weighs less than 5 lb and is only 1.1 inches thin.

- **Versatile Display**

Introducing a desktop and detachable monitor all in one, the perfect solution for any environment. With the DesXcape you will be able to access your e-mail, or work with applications from anywhere in or around your office.

- **Touch Panel with Virtual Keyboard**

Use this 15" LCD color display in a variety of applications with the touch panel and pop up virtual keyboard.

- **Wireless Keyboard**

DesXcape comes standard with a wireless keyboard providing additional input options for use in heavy-duty data input operations.

- **DVI/Dual input**

DesXcape is ready to receive either digital or analog video signals from high-end computer graphic cards.

- **Built In Rechargeable Battery**

The high capacity battery pack allows up to five hours of cordless connection.

- **Fast and Easy Setup**

Out of the box and ready to go, this detachable monitor offers an easy, user-friendly setup process.

- **Cool and Quiet Operation**

The DesXcape has been uniquely designed to optimize airflow for cool and quite fan-less operation.

- **Adjustable Tilt and Swivel Cradle**

Delivers optimal viewing angle suited to any user's needs.

- **Philips Limited Warranty**

One-call support includes a comprehensive 1-year 48-hour advance swap guarantee.



**Product Number** 150DM10P



## Technical Specifications

### Embedded System

- CPU Intel® Xscale™ Application Processor; 400MHz
- Memory 64MB SDRAM (on board)
- Flash ROM 32MB

### Operating System

- Microsoft® Windows® CE for Smart Displays

### Wireless Communications

- 802.11b wireless LAN (built in)

### LCD

- Panel TFT LCD
- Screen Size (inch/cm) 15.0 inch / 38.1 cm
- Pixel Pitch 0.297 x 0.297 mm
- Display Format 1024 x 768 pixels

### Touch Panel

- 12-bit A/D converter ; 100 samples per second

### Video

- Dual input interface Both Analog (D-Sub) and DVI-D are available and user selectable

### Panel Optical Characteristics

- Contrast Ratio 250:1 (typ.)
- Brightness 170 cd/m<sup>2</sup> (typ.)
- Viewing Angle V=90° Upper ≥ 30°(typ.)  
Lower ≥ 60°(typ.)  
H=100° Left ≥ 50°(typ.)  
Right ≥ 50°(typ.)

### Power Management

Complies with EPA Energy Star

### Buttons and Controls

- On Display
  - Power On/Off -slide switch
  - Brightness -VR dial
  - Volume -VR dial
  - Dashboard - launch button
  - Input Panel - launch button
  - Hardware Reset - push button
  - Software Reset - push button
  - R/F keyboard Reset - push button
  - OK - Tact Switch
  - Auto - Tact Switch
  - Up / Down - Tact Switch
  - Left / Right - Tact Switch

### I/O

- On display
  - VGA (mini jack) out
  - USB; type A (\*2 ; for keyboard and mouse)
  - Headphone jack
  - DC-in jack
  - Base station connector
  - Dual integral stereo 16 bit
  - AC 97 2.0 compliant speaker\*2
- On Base station DC-in jack
  - DVI-D (digital)
  - 15-pin Dsub (analog)
  - USB type B
  - USB; type A (\*2 ; for keyboard and mouse)
  - Audio-in jack
  - Audio-out jack

### Audio

- Stereo Speakers 1.5 W x2 RMS

### Included Accessories

- Battery
- AC-Adapter
- Stylus x 2
- Base station
- USB B to A cable
- VGA cable
- Mini VGA cable
- Audio cable
- USB Wireless network adaptor
- RF Key board (88 Keys) with Touch Pad

### Optional Accessories

- Extra AC adapter SG3AP174
- Stylus 3-pack SG3ST174
- Extra battery Pack SG3BA74

### Regulatory Approvals

- TÜV
- FCC-B, UL, CSA
- SEMKO
- CE Mark
- Energy Star
- USB Logo
- Microsoft® Windows® XP Pro LOGO
- Microsoft® Windows® CE for Smart Displays LOGO

### Others

- Security Port Kensington Lock Port Cable door Lock Port
- Wall mounting Standard VESA mounting (options) Pedestal hook easy mounting

\* Resolution 1028 x 768, standard size, contrast max., brightness 50%, 9300°K. Full white pattern, without Audio.

### Physical Specifications

- UPC Code 150DM10 0 37849 93407 4
- Display Dimensions (WxHxD) 14.7" x 12.1" x 1.1"  
375 x 309 x 28.5 mm (min height)
- Base Station Dimensions (WxHxD) 7.8" x 8.0" x 8.9"  
200 x 205 x 227 mm (min height)
- Display Weight 5.2 lbs/2.4 kg
- Base Station Weight 4.8 lbs/2.2 kg
- Carton Dimensions (WxHxD) 22.2" x 14.7" x 11.1"  
563 x 373 x 281 mm
- Carton Weight 20 lbs/ 9 kg
- Tilt -3°~25°
- Temperature (operating) +5°C to +35°C/ 9°F to 104°F
- Temperature (storage) -20°C to +60°C/ -4°F to 140°F
- Relative Humidity 20% to 80%

We recommend using 1024 x 768 at 60Hz non-interlaced mode for the best picture quality

**Carton Contains:** Two Stylus, Adjustable Docking Station, USB Wireless Network Adaptor, Li-ion Battery Pack, 88-Key Wireless Keyboard, AC Power Adaptor, USB B to A Cable, VGA Cable, DVI-D cable, Mini-VGA Adapter, Audio Cable and Quick Start Guide.

INTERNET ADDRESS: <http://www.philipsusa.com>  
TECHNICAL SUPPORT: (877) 835-1838 (USA)  
(402) 536-4171 (outside USA)

Specifications subject to change without notice.

Printed in the U.S.A., ©2003 Philips Consumer Electronics Co. A Division of Philips Electronics North America Corp. We recommend using 1024 x 768 at 60 Hz noninterlaced mode for the best picture quality. As an Energy Star partner, Philips has determined that this product meets the Energy Star guidelines for energy efficiency. Microsoft and Windows are registered trademarks of Microsoft Corporation "DCDi" is a trademark of Farudja, a division of Genesis Microchip Inc.  
CCM-141-4/03

**Literature Order Number:** 150DM10P

